

The Gauge House

MODEL 'SE-201LFW-EZ', EZ-READ GAUGES

Our 'SE-200LFW-EZ' Series Gauge Line Is A Quality Line Of Liquid Filled Gauges. The 'EZ-READ' Dial allows accurate and easy readings from a convenient distance. This is also beneficial for safety if there is a chance that the gauge may be overpressured – keeping inspectors out of harms way.

The Glycerine Filling Helps Dampen The Effects Of Pulsation And Vibration, While Also Perpetually Lubricating The Movement (And Keeping Contaminates Such As Dirt Away From All Moving Parts) Which Will Extend The Life Of The Gauge.

This Gauge Has Been Specifically Designed With The Original Equipment Manufacturers In Mind And Are Typically Used On Hydraulic & Pneumatic Systems As Well As Any Commercial Or Industrial Application Not Corrosive To Brass And Bronze Wetted Parts Where Glycerine Filling Is Suitable For Use.

SPECIFICATIONS:


- Available Dial Sizes: 2 1/2"
- Available Connection Sizes: 1/4"NPT
- Stainless Steel Case And Bezel
- Brass Internals & Connection
- Phosphour Bronze Bourdon Tube
- Liquid Filled
- Accuracy : Standard = 3-2-3 % Per ANSI grade B
- Dual Scale: PSI & Bar (x100=kPa)
- Ambient temperature: 30°F to 160°F



Notice how the 'EZ-READ' Dial allows clear, accurate and easy readings from a convenient distance. This is also beneficial for safety if there is a chance that the gauge may be overpressured – keeping inspectors out of harms way.



RANGE	CODE	Major In	Minor In
30/0"VAC	A	5	0.5
30/0/15	CB	5	0.5
30/0/30	CC	10	1
30/0/60	CD	10	1
30/0/100	CE	20	2
30/0/150	CF	20	2
30/0/300	CH	50	10
0/15	B	2	0.2
0/30	C	5	0.5
0/60	D	10	1
0/100	E	20	2
0/160	F	20	2
0/200	G	40	5
0/300	H	50	5
0/400	I	50	5
0/600	K	100	10
0/1000	M	200	20
0/1500	N	200	20
0/2000	O	400	50
0/3000	P	500	50
0/5000	R	1000	100
0/10,000	U	1000	100
0/15,000	V	2000	200



		A	B	C	D	E
2 1/2" Dial	In	2.80	1.28	1.07	3.55	1/4" Npt
	MM	71	33	27	90	

*Dimensions subject to change